This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (currently amended) A wireless communication unit (100, 200, 300, 400) for use in a digital radio communication system, said wireless communication unit comprising:

means for signal transmission (102, 104, 106), means for signal reception (108, 104, 106), a vocoder (132), a digital-to-analog converter (134), and

a microprocessor (110) characterized in that it also comprises ing a) means for storing messages (124) and b)said microprocessor (110), when activated, is adapted means to stop playing a currently received message while still recording said message in said means for storing messages (124) and c) means to start replaying said message stored in said means for storing messages (124) from a beginning of said message.

- 2. (currently amended) The wireless communication unit according to claim 1, wherein said means for storing messages comprises a first buffer (126) and a second buffer (130).
- 3. (currently amended) The wireless communication unit according to claim 2, wherein a memory (128) is connected to said first buffer and to said vocoder.
- 4. (original) The wireless communication unit according to claim 2, wherein a memory is connected to said second buffer and to said digital-to-analog converter.
- 5. (original) The wireless communication unit according to claim 2, wherein said vocoder upon reception of a signal from said microprocessor is adapted to stop playing said message from said first buffer and to start replaying said message from the beginning of said message, from said first buffer.

- 6. (original) The wireless communication unit according to claim 2, wherein said digital-to-analog converter upon reception of a signal from said microprocessor is adapted to stop playing said message from said second buffer and to start replaying said message from the beginning of said message, from said second buffer.
- 7. (original) The wireless communication unit, according to claim 3, wherein said vocoder upon reception of a signal from said microprocessor is adapted to stop playing said message from said first buffer and to start replaying said message from the beginning of said message, from said memory.
- 8. (original) The wireless communication unit according to claim 4, wherein said digital-to-analog converter upon reception of a signal from said microprocessor is adapted to stop playing said message from said second buffer and to start replaying said message from the beginning of said message, from said memory.
- 9. (currently amended) The wireless communication unit according to any one of the preceding elaimsclaim 1, wherein said microprocessor is adapted to initiate a transmission of a notification that the replay is activated.
- 10. (currently amended) The wireless communication unit according to any one of the preceding elaimsclaim 1 further comprising a dedicated replay switch (118) operably connected to the microprocessor.

- 11. (currently amended) A method of replaying a message received (502) in a wireless communication unit comprising the steps of:
- a) recording (504) said message in a means for storing messages while playing (506) said message in a speaker;

characterized in that said method further comprises the steps of:

- <u>be</u>) terminating said playing (506) of said message and continuing on receiving (502) and recording (504) of said message,
- <u>cd</u>) replaying (508)-said recorded message from the means for storing messages starting from a beginning of said message, while continuing with receiving (502) and recording (504)-said message.
- 12. (currently amended) The method according to claim 11, wherein said step of replaying starts after said step of terminating with a delay caused only by a response time of an electronic circuitry or processing time of thea vocoder.
- 13. (currently amended) The method according to claim 11-or claim 12, wherein said message is a simplex message.
- 14. (currently amended) The method according to any one of claims 11 to 13claim 11, wherein said step of termination is initiated by a user of said wireless communication unit.
- 15. (currently amended) The method according to any one of claims 11 to 14 claim 11, wherein said message, when terminated, is still recorded in a first buffer.
- 16. (original) The method according to claim 15, wherein said message is transferred from said first buffer to a memory.
- 17. (currently amended) The method according to any one of claims 11 to 14claim 11, wherein said message, when terminated, is still recorded in a second buffer.
- 18. (original) The method according to claim 17, wherein said message is transferred from said second buffer to a memory.
- 19. (original) The method according to claim 15, wherein said message is retrieved by a vocoder from said first buffer.

- 20. (original) The method according to claim 17, wherein said message is retrieved by a digital-to-analog converter from said second buffer.
- 21. (original) The method according to claim 16, wherein said message is retrieved by a vocoder from said memory.
- 22. (original) The method according to claim 18, wherein said message is retrieved by a digital-to-analog converter from said memory.
- 23. (currently amended) The method according to any one of claims 11 to 22claim 11, wherein when said message is completely received a notification on activation of the replay is transmitted to a sender of said message.
- 24. (currently amended) The method according to any one of claims 11 to 23 claim 11, wherein any new incoming call is signalized when the replay is active.
- 25. (cancelled)
- 26. (currently amended) The wireless communication unit according to any one of claims 1 to 10claim 1, wherein said wireless communication unit is a TETRA radio or an ASTRO/APCO 25 radio or an IDEN radio.